

# NORTEX<sup>®</sup>

## EQUIPMENT FOR TEXTURED COATINGS



TX30



TX20

by **NOREXCO<sup>®</sup>**

# NORTEX<sup>®</sup> TX20



TX20

**NORTEX<sup>®</sup> TX20** is a unit designed for the application of decorative textured coatings, as well as thick plastic-based coatings and some lighter coatings used for façades.

**NOREXCO<sup>®</sup>** has developed this unit for textured coatings in order to meet the requirements of professionals looking for a **powerful, yet lightweight piece of equipment**.

All the components of the **NORTEX<sup>®</sup> TX20** unit have been chosen very carefully and rigorously, in order to assure an excellent reliability and lifetime.

**NORTEX<sup>®</sup> TX20** must always be used with an **AIRPLUS<sup>®</sup> AP24** compressor or any other compressor producing a continuous air output of at least 10m<sup>3</sup>/h at 4 bars.

#### Key advantages:

- **Very light and extremely easy to handle, therefore suited for all types of job sites.**
- **Base-frame and hopper in stainless steel**, guarantying the longest possible lifetime of your equipment.
- **Base-frame mounted on two large inflatable wheels and two small wheels**, enabling you to move the unit around in any configuration.
- **The hopper is easy to remove from the base-frame**, assuring maximum access to the bottom of the hopper for in-depth cleaning, maintenance and repairs. Water-tightness guarantied by a special reinforced and highly resistant rubber gasket.
- **Bottom of hopper equipped with a valve**, for quick and efficient cleaning.
- **Extremely compact unit.**

- **Electrical equipment mounted in an IP65** chock-resistant and waterproof box. Control panel is simple and easy to operate.
- **Output flow can be adjusted very precisely** by a potentiometer.
- **Pneumatic remote control** of the motor, automatic at the opening / closing of the texture coating gun.
- **Regulator with moisture separator**, integrated on the hopper, assuring a precise adjustment of the air pressure depending on the type of finishing required.

#### TECHNICAL SPECIFICATIONS AND EQUIPMENT

Output .....	0 to 12 kg/min
Capacity .....	3 bags
Supply .....	220 V / 6 A
Motor power supply.....	0,75 kW
Maximum granulometry .....	4 mm
Tips .....	Ø 4,5 and 6
Air and product hose.....	Product 10 M - Ø 25 Air 10 M - Ø 10
Air supply hose .....	5 m - quick coupling
Electrical cable .....	5 m - 3x2,5 mm <sup>2</sup> HO7RNF
Gun .....	ABS with conical brass piston
Cleaning ball .....	2 balls to clean out the product hose
Dimensions : Length.....	930 mm
Width .....	490 m
Height.....	630 mm
Weight.....	43 kg

# NORTEX® TX30



TX30

**NORTEX® TX30** is a unit designed for the application of decorative textured coatings, as well as thick plastic-based coatings and some lighter coatings used for façades.

**NOREXCO®** has developed this unit for textured coatings in order to meet the requirements of professionals looking for a **very powerful piece of equipment with a high level of autonomy.**

All the components of the **NORTEX® TX30** unit have been chosen very carefully and rigorously, in order to assure an excellent reliability and lifetime.

**NORTEX® TX30** must always be used with an **AIRPLUS® AP24** compressor or any other compressor producing a continuous air output of at least 19m<sup>3</sup>/h at 4 bars.

#### Key advantages:










- **High capacity and high output for maximum efficiency on larger job sites.**
- **Base-frame and hopper in stainless steel,** guarantying the longest possible lifetime of your equipment.
- **Base-frame mounted on two large inflatable wheels and two small wheels,** enabling you to move the unit around in any configuration.
- **The hopper is easy to remove from the base-frame,** assuring maximum access to the bottom of the hopper for in-depth cleaning, maintenance and repairs. Water-tightness guarantied by a special reinforced and highly resistant rubber gasket.
- **Bottom of hopper equipped with a valve,** for quick and efficient cleaning.
- **Extremely compact unit.**


- **Electrical equipment mounted in an IP65** chock-resistant and waterproof box. Control panel is simple and easy to operate.
- **Output flow can be adjusted very precisely** by a potentiometer.
- **Pneumatic remote control** of the motor, automatic at the opening / closing of the texture coating gun.
- **Regulator with moisture separator,** integrated on the hopper, assuring a precise adjustment of the air pressure depending on the type of finishing required.

#### TECHNICAL SPECIFICATIONS AND EQUIPMENT

Output .....	0 to 16 kg/min
Capacity .....	5 bags
Supply .....	220 V / 7 A
Motor power supply.....	0,75 kW
Maximum granulometry .....	4 mm
Tips .....	Ø 4,5 and 6
Air and product hose.....	Product 10 M - Ø 25 Air 10 M - Ø 10
Air supply hose .....	5 m - quick coupling
Electrical cable .....	20 m - 3x2,5 mm <sup>2</sup> HO7RNF
Gun.....	Aluminium with conical brass piston
Cleaning ball .....	2 balls to clean out the product hose
Dimensions : Length.....	1020 mm
Width .....	610 mm
Height.....	870 mm
Weight.....	65 kg

# NORTEX® ACCESSORIES

	REF.	DESCRIPTION
	<b>NP1700</b> <b>NP1800</b>	Bag roller for <b>NORTEX® TX20</b> Bag roller for <b>NORTEX® TX30</b>
	<b>NP1510</b> <b>NP1520</b> <b>NP1530</b> <b>NP1540</b> <b>NP1550</b> <b>NP1560</b> <b>NP1535</b> <b>NP1531</b> <b>NP1532</b> <b>NW9084</b> <b>NW9085</b>	Complete hose air/product Ø 25 - 10 M Complete extension air/product Ø 25 - 5 M Complete hose air/product Ø 19 - 10 M Complete extension air/product Ø 19 - 5 M Complete hose air/product Ø 32 - 10 M Complete extension air/product Ø 32 - 5 M Adapter coupling kit for NP1530 Reduction 1"F x 3/4" M Reduction 1"M x 3/4" F Adapter M x 3/4" F Adapter M x 3/4" M
	<b>NW9160</b>	Complete ABS gun with cam-coupling and tip Ø 6
	<b>NW9150</b>	ABS gun bare
	<b>NW9060</b>	Aluminium gun with cam-coupling and tip Ø 6
	<b>NW9140</b> <b>NW4009</b> <b>NW4010</b> <b>NW4011</b> <b>NW4012</b> <b>NW4013</b> <b>NW4014</b> <b>NW4015</b> <b>NW4016</b> <b>NW4017</b>	Aluminium gun bare Tip Ø 3 Tip Ø 4 Tip Ø 5 Tip Ø 6 Tip Ø 7 Tip Ø 8 Tip Ø 10 Tip Ø 12 Tip Ø 14
	<b>NW8120</b> <b>NW8121</b> <b>NW8050</b> <b>NW8051</b>	Rotor for <b>NORTEX® TX20</b> Stator for <b>NORTEX® TX20</b> Rotor for <b>NORTEX® TX30</b> Stator for <b>NORTEX® TX30</b>
	<b>NW1602</b> <b>NW1603</b> <b>NP1415</b> <b>NP1610</b>	Cleaning ball Ø 30 Cleaning ball Ø 40 Grease cartridge Pump pressure control kit



**NOREXCO®**

**NOREXCO S.A.**

16, rue des Chasseurs - Z.I. Internationale

74100 Ville-la-Grand - France

Tel. +33 (0) 4 50 38 37 36 - Fax +33 (0) 4 50 92 88 44 - E-mail: norexco.france@norexco.com



YOUR DEALER: